

## SELECTION & SPECIFICATION DATA

<b>Generic Type</b>	Surface cleaner
<b>Description</b>	The product is a biologically degradable liquid without any hazardous substances. It is approved as a HOCNF Class Yellow product, and can be disposed to drains/sewage systems without containment. Active ingredients are citric acid, phosphoric acid, inhibitor and water. It has a light red colour, sour smell and a pH value of 1,1 til 1,7 with density 1.14 g/cm <sup>3</sup> .
<b>Features</b>	Carboclean Cons 200 is used to remove oxides (rust), chalk, magnetite, humus, salt, concrete, shell, algae and other deposits. Well-suited for internal treatment of pipes and piping systems made of metals and plastic-/polyester products. Does not damage paints, plastics, metals, linings or packings.
<b>Color</b>	Light red
<b>Physical Properties</b>	pH: 1,1 – 1,7 Weight per litre: 1,14 kg Freezing point: - 4°C Storage temperature: - 4°C to 50°C Solubility in water: Fully soluble

## MIXING & THINNING

<b>Working Time</b>	Time to work (at 20°C, 50% RH): Approx 2- 24 hours Varies with temperature and mixing ratio.
---------------------	---

## APPLICATION EQUIPMENT GUIDELINES

Listed below are general equipment guidelines for the application of this product. Job site conditions may require modifications to these guidelines to achieve the desired results.

<b>General</b>	Professional use of the product requires training. A work procedure for professional users is available. PRETREATMENT: The surface shall be free of oil, fat etc.. Corroded areas with lumps of rust and similar should be picked, scraped or wire brushed to grade St. 2-3 according to standard ISO 8501 SIS 055900. The product should not be used on thermally sprayed and zinc galvanized surfaces.  APPLICATION: Apply Carboclean Cons 200 evenly. Let it work for approx. 2- 24 hours. Varies with temperature and mixing ratio. Recommended mixing ratio is 1:1 to 1:10 by volume. Then remove Carboclean Cons 200 using high-pressure warm water cleaning. Carboclean Cons 200 can also be used for cleaning objects in bath and for flushing of pipeline systems.
----------------	---

<b>Airless Spray</b>	Airless spray nozzles: 0,025" - 0,033"
----------------------	--

<b>Application Tool</b>	Professionals use airless spray. Alternatively use brush or roller.
-------------------------	---

## CLEANUP & SAFETY

<b>Cleanup</b>	Water
----------------	-------

# Carboclean Cons 200

## PRODUCT DATA SHEET



## CLEANUP & SAFETY

### Safety

**RECOMMENDED PERSONAL PROTECTION EQUIPMENT:** Please refer to detailed information in safety data sheet. Respiratory protection with rechargeable filters must be used in areas with inadequate ventilation. Use dust filter P3 (for fine dust). Wear chemical resistant gloves complying with EN 374 made of PVC, natural rubber or latex. Tightly fitting safety goggles or face shield. Face shield or full face respirator must be used when spraying and aerosols are formed. Fully covering, long sleeved protective clothing must be used.

## PACKAGING, HANDLING & STORAGE

**Shelf Life** | 24 months at 24C

**Packaging** | 5 litres, 25 litres, 1000 litres (IBC)

## WARRANTY

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Carboline Company to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Carboline quality control. We assume no responsibility for coverage, performance, injuries or damages resulting from use. Carbolines sole obligation, if any, is to replace or refund the purchase price of the Carboline product(s) proven to be defective, at Carbolines option. Carboline shall not be liable for any loss or damage. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY CARBOLINE, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. All of the trademarks referenced above are the property of Carboline International Corporation unless otherwise indicated.